

## DECLARATION OF PERFORMANCE (DoP)

**1. Unique identification code of the product type:**

Solidcor R30 Glazed & Unglazed Fire Door System

**2. Intended use:**

To be used as an FD30S Doorset either internally or externally providing 30 minutes resistance to fire and smoke when fabricated, fitted and maintained in accordance with the manufacturer's instructions.

**3. Manufacturer:**

Solidcor Ltd, Unit 5 Sheepbridge Works, Sheepbridge Lane, Chesterfield, S41 9RX

**4. Notified body:**

IFC Certification No.1720

**5. Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Resistance to Fire (E/I/W)	E30	EN16034:2014
Smoke Control (Sa/S200)	Sa	
Self-closing	C	
Durability	5	
Air permeability	Class 4	EN14351-1:2006+A2:2016
Watertightness	Class 3A	
Resistance to wind load	Class A2	
Vertical Load	Class 2	
Static Torsion	Class 2	
Soft & heavy body impact	Class 2	
Hard body impact	Class 2	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ashley Smith

on 1<sup>st</sup> May 2024

